



# Ururu streamer technology air purifier

MCK70ZH



Humidification



Flash Streamer

DAIKIN



Onecta via app

## Humidification and air purification in one

- › Onecta app
- › Air purification for large spaces up to 96 m<sup>2</sup>
- › Daikin's Catch and Clean approach
- › Intuitive display design

- › Whisper quiet
- › High performance electrostatic HEPA filter
- › Filter lifetime of ten years

MCK70ZH



Indoor Unit				MCK	70ZH
Application					Floor standing type
Applicable room area				m²	48 (1) / 96 (2)
CADR				m³/h	375 (3)
Weight				Unit	kg
Dimensions				Height x Width x Depth	mm
Casing				Colour	Gray (2.4PB/3.9/0.7)
Fan				Type	Multi Blade Fan (Sirocco fan)
				Air flow rate	84 /132 /210 /420
				Air purifying operation	Silent/Low/Medium/Turbo
				Humidifying operation	Silent/Low/Medium/Turbo
Sound pressure level (5)				Air purifying operation	18 /27 /37 /54
				Humidifying operation	18 /27 /37 /54
Humidifying operation				Power input	0.010 /0.012 /0.023 /0.084
				Humidification	Turbo
				Water tank capacity	700 (4)
					3.4
Air purifying operation				Power input	0.010 /0.011 /0.020 /0.082
Deodorizing method					Flash streamer + Deodorizing catalyst
Dust collecting method					Electrostatic HEPA filter (7)
Air filter				Type	Polyethylene terephthalate net
Sign				Item	01
					Humidity monitor lamp: 5 stages / PM 2. 5 sensor lamp: 3 stages / Odour sensor lamp: 3 stages / Humidity setting: Low/Standard/High / AUTO FAN mode / Econo mode / Anti-pollen mode / MOIST mode / CIRCULATION mode / Child proof lock lamp / Water supply lamp / AUTO operation lamp / Streamer lamp / AIR MONITOR indicator: 0µg/m3 - 99µg (8) /m3 / 0°C - 39°C,20% - 90% / FAN lamps: Quiet/Low/Standard/Turbo / Humidifier ON/OFF lamp / Daikin eye / AIR MONITOR setting lamps / Communication lamp
Power supply				Phase/Frequency/Voltage	1~/50/60/220-240/220-230
Type					Humidifying air purifier

(1) The coverage area is appropriate for operating the unit of maximum fan speed(HH).Coverage area indicates the space where a certain amount of dust particles can be removed in 30 minutes. |

(2) Converted to NRCC standards from test values in accordance with JEM1467. |

(3) Converted to CADR standards from test values in accordance with JEM1467. |

(4) Humidification amount changes in accordance with indoor and outdoor temperature and humidity. Measurement condition: 20°C in temperature, 30% in humidity. |

(5) Operating sound levels are the average of values measured at 1m away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) |

(6) Electrostatic HEPA filter and humidifying filters are attached in the unit. |

(7) Requirements according to JEM1467. |

(8) "HI" is displayed when the PM2.5 concentration exceeds 99µg/m3.

